Using Neutrinos from the Booster Beamline in the SciBooNE hole

Zelimir Djurcic

Argonne National Laboratory

in collaboration with

G. Davies (Iowa State), H. Frisch (U Chicago) M. Sanchez (Iowa/ANL), M. Wetstein (U Chicago/ANL), T. Xin (Iowa State)





2011

Content of this Presentation


- -Booster beamline info.
- -Location of the former SciBooNE enclosure.
- -Dimensions of the enclosure.
- -Neutrino flux from the Booster beamline at the enclosure.
- -Calculation of the rate of neutrino interactions in oil and water.
- -Goals.


Fermilab Neutrino Beams








Booster Beamline and SciBooNE Hole












Booster Neutrino Beam



8.9 GeV proton beam momentum on Beryllium target.


External measurements (HARP, etc) used to describe hadron production.

Neutrino Flux modeled with GEANT4 simulation.

Booster runs in both neutrino and anti-neutrino modes.

Details: "The Neutrino Flux prediction at MiniBooNE", by MiniBooNE Collaboration (A.A. Aguilar-Arevalo et al.), Phys.Rev.D79:072002,2009., arXiv:0806.1449 [hep-ex].00

Booster Neutrino Flux at SciBooNE Location



- -neutrino mode flux (the beam also runs in anti-neutrino mode).
- -Flux calculated per unit area [cm²] per 10⁶ protons on Booster target, by averaging over cycle with R=150 cm.


Cross-section for calculating Event Rates


Cross-section generator = Nuance

Nuance describes various neutrino interaction processes on CH₂/H₂O, which include:

- -Llewellyn-Smith free nucleon quasi-elastic cross section,
- -Rein-Seghal resonant and coherent pion production cross section,
- -Smith-Moniz Fermi gas model,
- -final state interactions based on π -Carbon scattering data,
- -etc.

Example: Cross-section for v_{μ} charged current (CC) interaction at CH_2





Next pages shows total expected event rate (before reconstruction is applied), including all interaction channels for $1x10^{20}$ POT exposure.

Assumed:

Mass = 1 ton (just multiply to desired tonnage).


Target = CH_2 , density = 0.855 g/cm³, or

Target = H_2O , density = 1.0 g/cm³.

Cross-section generator = Nuance

Event Rates

-Calculate event rates (flux x cross-section)



Rates Expected with 1x10²⁰ POT exposure

	Total Events [1/1ton/10 ²⁰ POT]	ν-type	Total (per v-type)	Charged Current	Neutral Current
Booster Beam	10419	v_{μ}	10210	7265	2945
(ν-mode,		anti- ν_{μ}	133	88	45
Target = CH_2)		$v_{\rm e}$	72	52	20
		anti-v _e	4.4	3	1.4
Booster Beam	10612	v_{μ}	10405	7443	2962
(v-mode,		anti- ν_{μ}	129	85	44
Target = H_2O)		$v_{\rm e}$	73	53	20
		anti-v _e	4.6	3.0	1.6

What to expect in a run with LAPD prototype at SciBooNE location?

- -Currently Booster delivers ~1.2x10²⁰ POT/year.
- -In 2013 the Booster will be running for MicroBooNE. They expect \sim (2 to 3)x10²⁰ POT/year.
- -Booster beam will (most likely) run in neutrino mode.
- -In the calculations performed the flux uncertainty is 10%, the cross-section uncertainties are more than 10%.
- -Easy to calculate flux and event rates in anti-neutrino mode (not done here). Rates would be ~5 times lower in anti-neutrino mode when compared to neutrino mode.

Goals (not in the particular order)

- -Measure neutrino cross-sections in water (important for LBNE); essentially unmeasured in this energy range.
- -Measure neutron yield in neutrino interactions (bkg from atmospheric neutrino interactions -> proton decay).
- -Use both water and water-based LS (LS can detect muons below muon's cherenkow threshold in pure H2O, etc).
- -Do all this with new LAPPDs.